

BS 30 Two-cycle Vibratory Rammer

Item Number: 0005216

BS 30

WACKER's WM 80, 2-stroke engine, built for tough rammer applications

>> Wacker Neuson rammers have set the standard in the construction industry. These rammers are powered by the exclusive WM 80, the only 2-stroke engine specifically designed and built for vibratory rammers and meets EPA air emissions standards. Wacker Neuson's rugged rammers are designed for maximum production, performance and durability. <<



Additional Advantages

- Designed for special back-fill applications and equipped with economical energy-saving single drive.
- Driven by powerful Wacker Neuson-2-stroke gasoline engine flanged directly to the casing.
- Centrifugal clutch ensures easy starting.
- Easy handling due to vibration-damped guide handle.
- Sturdy, tried and tested ramming system.
- Ramming shoe equipped with steel bottom sheet resistant to wear.

Description	Metric	Imperial
Length x width x height	540 x 340 x 1.000 mm	21.3 x 13.4 x 39.4 in
Shoe size (w x l)	150 x 280 mm	5.0 x 11.0 in
Operating weight	32 kg	70.6 lb
Ramming shoe stroke	approx. 42 mm	approx. 1.7 in
Percussion rate	830 1/min	830 blows/min
Drive engine	air-cooled 2-stroke gasoline engine	
Manufacturer	Wacker Neuson	Wacker Neuson
Model	WM 80	
Displacement	80 cm ³	4.9 in ³
Fuel type	gasoline-oil mixture 50:1	gasoline-oil mixture 50:1
Fuel consumption	approx. 0,45 l/h	approx. 0.12 US gal/h
Tank capacity	2,2 l	2.3 US qt

Standard Package - BS 30

Includes guide handle roller,
operator's manual and parts book.

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Tuesday, December 14, 2010

